

GPS-IMEASURE-D™

Duct Mounted Ion Meter

PRODUCT DESCRIPTION

The GPS-IMEASURE-D ion detector is permanently mounted in the duct or inside an air handling system downstream of any GPS Air's ionization device. It includes three sensitivity levels of 10,000/100,000/1,000,000 ions/cc that can be set based on the application and mounting location.

STANDARD FEATURES

Auto calibration, auto zero, 0-10 VDC analog output for Building Automation System (BAS) monitoring 24/7, watchdog timer, bi-color operation status LED, field selectable ion sensing range as well as a jumper for BAS selectable polarity sensing.

INSTALLATION

- Can be used with any of GPS Air's ionization systems



SPECIFICATIONS

Input Voltage	20 - 40 VDC or VAC	Ion Sensing Range	0-10k, 0-100k, 0-1M ions/cc (+ve or -ve)
Current	20mA	Polarity	Field selectable positive or negative
Power Consumption	2.4 Watts	Humidity Range	0 - 95% RH non-condensing
Output Impedance	1 Kohm	Temperature Range	0 - 148°F
Unit Dimensions	Housing: 5.25"L x 6.25"W x 2.0"H Sensing Rod: 10.5"L x 2" Dia.	Air Flow Capacity	1,000 - 100,000 CFM
Output Voltage	0 - 10 VDC; scaled to selected ion-sensing range	Duct Velocity	300 - 1,100 FPM



www.gpsair.com