

# GPS-NEMA4-OE™

*NEMA 4X Control Panel*

## PRODUCT DESCRIPTION

The GPS-NEMA4-OE is a NEMA 4X rated fiberglass enclosure designed to house one GPS-iMOD power supply. The panel adds a superior finished look to any project while providing the required protection against foreign substances such as water and dust when the power supplies are mounted in non-NEMA 1 rated environment.

## STANDARD FEATURES

System performance indications: Illuminated On/Off Switch, Power On and System Off indicators.

## INSTALLATION

- Indoor or Outdoor
- Required only when the GPS-iMOD power supply is in wet, dirty or otherwise non-NEMA 1 rated environments.



## SPECIFICATIONS

<b>Input Voltage (AC Only*)</b>	24V/120V/208-240V	<b>Output Current</b>	3 mA for GPS-iMOD
<b>GPS-iMOD Amps</b>	0.63A @ 24V, 0.13A @ 120V, 0.07A @ 208-240V	<b>Power Entry</b>	Power Entry 1/4" Heyco Liquid-Tight Connector
<b>Power Consumption</b>	15 Watts for GPS-iMOD	<b>Compliance &amp; Certifications</b>	OSHPD Seismic (OSP), NEMA 4X
<b>Frequency</b>	50/60Hz	<b>Weight</b>	13.99 lbs with power supply 9.36 lbs without power supply
<b>Output Voltage</b>	5.0kV RMS for GPS-iMOD		

\*GPS-iMOD can accept 24V to 240V

