

# PS-2™

*Dedicated Power Supply Transformer for Needlepoint Ionizers*



## PRODUCT DESCRIPTION

The PS-2 is a single power transformation solution for GPS Air's compatible air ionization systems

## STANDARD FEATURES

Multi-voltage input, 24VDC output, integral Building Automation System (BAS) alarm contact pass through, 7/8" hole sized for 1/2" trade size conduit fittings on power entry side, 5/8" hole sized for 3/8" trade size conduit fittings on power exit side.



## INSTALLATION

- Designed for use in plenum and non-plenum spaces.

## SPECIFICATIONS

<b>Ionizers supported</b>	CI-2, DM-2	<b>Humidity Range</b>	0 - 100% RH
<b>Input Voltage</b>	110-277V AC	<b>Unit Dimensions</b>	7.4" L x 1.6" T x 2.4" W
<b>Output Voltage</b>	24 VDC	<b>Weight</b>	0.45 lb
<b>Frequency</b>	50/60HZ	<b>Electrical Approvals</b>	UL, cUL
<b>Temperature Range</b>	-20°F to 140°F	<b>Alarm Contact Rating</b>	250VAC / 1A, N.O. "dry" contact (pass through)
		<b>Compliance &amp; Certifications</b>	UL 1310 (Class 2 Power Unit)

